EXHAUST EMISSION DATA SHEET

MQ POWER GENERATOR SET



Model: DCA-25SSIU2

The engine used in this generator set is certified to comply with United States EPA Tier 2 and CARB Mobile Off-Highway emission regulations.

ENGINE DATA

Model: ISUZU AA-4LE2 Bore: 3.35 in. (85 mm)

Type: 4-Cycle, In-Line, 4-Cylinder, Diesel Stroke: 3.78 in. (96 mm)

Aspiration: Naturally Aspirated Displacement: 133 cid (2.18 liters)

Compression Ratio: 18:1

PERFORMANCE DATA

SAE Gross HP @ 1800 RPM (60 Hz) 36
Rated Load Fuel Consumption (gal/Hr) 1.44
Rated Load Exhaust Gas Flow (cfm) 144
Rated Load Exhaust Gas Temperature (F) 1058

United States EPA - Mobile Off-Highway Tier 2 Limits - ≥25 BHP- ≤48 BHP		
Criteria Pollutant	Emission Requirements	Certified Engine Emissions
NOx (Oxides of Nitrogen as NO2)	(7.08)* gr/bhp-hr	(5.22)* gr/bhp-hr
HC (Total Unburned Hydrocarbons)	(NOx + HC)* Combined	(NOx + HC)* Combined
CO (Carbon Monoxide)	4.10 gr/bhp-hr	1.79 gr/bhp-hr
PM (Particulate Matter)	0.59 gr/bhp-hr	0.23 gr/bhp-hr

EPA Engine Family: 4SZXL02.2DNB

EPA Certificate of Conformance: SZX-NR3-04-08

Effective Date: Year 2004

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.