

EXHAUST EMISSION DATA SHEET

MQ POWER GENERATOR SET

Model: DCA-400SSK3



The engine used in this generator set is certified to comply with United States EPA Tier 2 and CARB Mobile Off-Highway emission regulations.

ENGINE DATA

Model:	KOMATSU SA6D140E-3	Bore:	5.50 in. (140 mm)
Type:	4-Cycle, In-Line, 6-Cylinder, Diesel	Stroke:	6.50 in. (165 mm)
Aspiration:	Turbocharged, Aftercooled	Displacement:	930 cid (15 liters)
		Compression Ratio:	16:1

PERFORMANCE DATA

STANDBY

PRIME

SAE Gross HP @ 1800 RPM (60 Hz)	560	490
Rated Load Fuel Consumption (gal/Hr)	27.3	24.3
Rated Load Exhaust Gas Flow (cfm)	2542	2436
Rated Load Exhaust Gas Temperature (F)	1013	853

United States EPA - Mobile Off-Highway Tier 2 Limits - ≥ 302 BHP - ≤ 602 BHP

Criteria Pollutant	Emission Requirements	Certified Engine Emissions
NOx (Oxides of Nitrogen as NO ₂)	(4.77)* gr/bhp-hr	(4.40)* gr/bhp-hr
HC (Total Unburned Hydrocarbons)	(NOx + HC)* Combined	(NOx + HC)* Combined
CO (Carbon Monoxide)	2.61 gr/bhp-hr	0.30 gr/bhp-hr
PM (Particulate Matter)	0.15 gr/bhp-hr	0.08 gr/bhp-hr

EPA Engine Family: 4KLXL15.2EC3
EPA Certificate of Conformance: KLX-NR7-04-16
Effective Date: Year 2004

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.