

EXHAUST EMISSION DATA SHEET

MQ POWER GENERATOR SET

Model: DCA-400SSVU



The engine used in this generator set is certified to comply with United States EPA Tier 2 and CARB Mobile Off-Highway emission regulations.

ENGINE DATA

Model:	AB VOLVO PENTA TAD1241GE	Bore:	5.16 in. (131 mm)
Type:	4-Cycle, In-Line, 6-Cylinder, Diesel	Stroke:	5.91 in. (150 mm)
Aspiration:	Turbocharged, Charge Air Cooler	Displacement:	740 cid (12 liters)
		Compression Ratio:	17.5:1

PERFORMANCE DATA

SAE Gross HP @ 1800 RPM (60 Hz)	527
Rated Load Fuel Consumption (gal/Hr)	20.6
Rated Load Exhaust Gas Flow (cfm)	2543
Rated Load Exhaust Gas Temperature (F)	914

United States EPA - Mobile Off-Highway Tier 2 Limits - ≥ 302 BHP - ≤ 602 BHP

Criteria Pollutant	Emission Requirements	Certified Engine Emissions
NOx (Oxides of Nitrogen as NO ₂)	(4.77)* gr/bhp-hr	(4.33)* gr/bhp-hr
HC (Total Unburned Hydrocarbons)	(NOx + HC)* Combined	(NOx + HC)* Combined
CO (Carbon Monoxide)	2.61 gr/bhp-hr	0.52 gr/bhp-hr
PM (Particulate Matter)	0.15 gr/bhp-hr	0.07 gr/bhp-hr

EPA Engine Family: 5VPXL12.1ACB
EPA Certificate of Conformance: VPX-NR7-05-10
Effective Date: Year 2006 **ENGINE FLEXIBILITY PROGRAM**

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.