EXHAUST EMISSION DATA SHEET

MQ POWER GENERATOR SET



Model: DCA-60SSI2

The engine used in this generator set is certified to comply with United States EPA Tier 1 and CARB Mobile Off-Highway emission regulations when tested per ISO 8178 D2.

FNG	INE	DV-	ГΛ
CING		DΑ	М

Model: ISUZU 6BG1 Bore: 4.13 in. (105 mm)

Type: 4-Cycle, In-Line, 6-Cylinder, Diesel Stroke: 4.92 in. (125 mm)

Aspiration: Naturally Aspirated Displacement: 396 cid (6.5 liters)

Compression Ratio: 17:1

PERFORMANCE DATA	STANDBY	<u>PRIME</u>
SAE Gross HP @ 1800 RPM (60 Hz)	94	84
Rated Load Fuel Consumption (gal/Hr)	3.1	2.8
Rated Load Exhaust Gas Flow (cfm)	477	468
Rated Load Exhaust Gas Temperature (F)	847	619

United States EPA - Mobile Off-Highway Tier I Limits - ≥49 BHP- ≤99 BHP				
Criteria Pollutant	Emission Requirements	Certified Engine Emissions		
NOx (Oxides of Nitrogen as NO2)	6.90 gr/bhp-hr	6.26 gr/bhp-hr		
HC (Total Unburned Hydrocarbons)	gr/bhp-hr	gr/bhp-hr		
CO (Carbon Monoxide)	gr/bhp-hr	gr/bhp-hr		
PM (Particulate Matter)	gr/bhp-hr	gr/bhp-hr		

EPA Engine Family: 2SZXL06.5BNA

EPA Certificate of Conformance: SZX-NR5-02-04

Effective Date: Year 2002

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.