MQ POWER GENERATOR SET



Model: DCA-70SSJU2

The engine used in this generator set is certified to comply with United States EPA Tier 1 and CARB Mobile Off-Highway emission regulations when tested per ISO 8178 D2.

	NE	DV.	TΛ
IUI	INC	DΑ	IA

Model: JOHN DEERE 4045TF150 Bore: 4.19 in. (106 mm)

Type: 4-Cycle, In-Line, 4-Cylinder, Diesel Stroke: 5.00 in. (127 mm)

Aspiration: Turbocharged Displacement: 276 cid (4.5 liters)

Compression Ratio: 17:1

PERFORMANCE DATA	STANDBY	<u>PRIME</u>
SAE Gross HP @ 1800 RPM (60 Hz)	113	102
Rated Load Fuel Consumption (gal/Hr)	5.3	4.8
Rated Load Exhaust Gas Flow (cfm)	522	487
Rated Load Exhaust Gas Temperature (F)	1050	979

United States EPA - Mobile Off-Highway Tier I Limits - ≥100 BHP- ≤173 BHP						
Criteria Pollutant	Emission Requirements	Certified Engine Emissions				
NOx (Oxides of Nitrogen as NO2)	6.90 gr/bhp-hr	5.45 gr/bhp-hr				
HC (Total Unburned Hydrocarbons)	gr/bhp-hr	gr/bhp-hr				
CO (Carbon Monoxide)	gr/bhp-hr	gr/bhp-hr				
PM (Particulate Matter)	gr/bhp-hr	0.21 gr/bhp-hr				

EPA Engine Family: 2JDXL06.8047

EPA Certificate of Conformance: JDX-NR6-02-30

Effective Date: Engines Manufactured On/After April 15, 2002

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.