

# EXHAUST EMISSION DATA SHEET

## MQ POWER GENERATOR SET

Model: DCA-800SSK



The engine used in this generator set is certified to comply with United States EPA Tier 1 and CARB Mobile Off-Highway emission regulations when tested per ISO 8178 D2.

### ENGINE DATA

Model:	KOMATSU SA12V140-1	Bore:	5.50 in. (140 mm)
Type:	4-Cycle, In-Line, 12-Cylinder, Diesel	Stroke:	6.50 in. (165 mm)
Aspiration:	Turbocharged, Aftercooled	Displacement:	1860 cid (30.5 liters)
		Compression Ratio:	14:1

### PERFORMANCE DATA

SAE Gross HP @ 1800 RPM (60 Hz)	1124
Rated Load Fuel Consumption (gal/Hr)	43.7
Rated Load Exhaust Gas Flow (cfm)	6250
Rated Load Exhaust Gas Temperature (F)	874

### United States EPA - Mobile Off-Highway Tier 1 Limits - >751 BHP

Criteria Pollutant	Emission Requirements	Certified Engine Emissions
NOx (Oxides of Nitrogen as NO <sub>2</sub> )	6.90 gr/bhp-hr	6.18 gr/bhp-hr
HC (Total Unburned Hydrocarbons)	0.97 gr/bhp-hr	0.67 gr/bhp-hr
CO (Carbon Monoxide)	8.50 gr/bhp-hr	0.67 gr/bhp-hr
PM (Particulate Matter)	0.40 gr/bhp-hr	0.15 gr/bhp-hr

EPA Engine Family: 3KLXL30.5GC1  
EPA Certificate of Conformance: KLX-NR9-03-25  
Effective Date: Year 2003

*Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.*