EXHAUST EMISSION DATA SHEET

MQ POWER GENERATOR SET

Model: DCA300SSJU4F3/B/PB/PD



The engine used in this generator set is certified to comply with United States EPA Tier 4 and CARB Mobile Off-Highway emission regulations.

	TA							
Manufacturer:	JOHN DEERE			Bore:	4.66	in.	(118	mm)
Model:	6090HFG06			Stroke:	5.35	in.	(136	mm)
Туре:	4-Cycle, In-Line, 6-Cylinde	er, Diesel		Displacement	549	cid	(9.0	liters)
Aspiration:	Turbocharger, ECM, EGR Injection, Charge Air Cool		CR Electronic Direct	Compression	Ratio:		16.0	:1
PERFORMA	NCE DATA							
SAE Gross HP	@ 1800 RPM (60 Hz) Ra	ted 43	7					
Load Fuel Con	sumption (gal/Hr) Rated	16	.7					
Load Exhaust	Gas Flow (cfm) Rated Lo	bad 14	48					
	emperature (°F)	83	1					
	• • • •							
United States EPA - Mobile Off-Highway Tier 4 Limits - 174								
Crite	ria Pollutant	Emis	sion Requirements	Certifie	d Engi	ne E	missic	ons
NOx (Oxides o	f Nitrogen as NO2)	0.298	gr/bhp-hr	0.074	gr/b	hp-hr		
HC (Total Unbu	urned Hydrocarbons)	N/A	gr/bhp-hr	N/A	gr/bl	hp-hr		
					ا ما/ س	I		
NOx + HC (Co	mbined)	N/A	gr/bhp-hr	N/A	gr/bi	hp-hr		
NOx + HC (Co CO (Carbon M	•	N/A 2.60	gr/bhp-hr gr/bhp-hr	N/A 0.007	•	np-nr hp-hr		
•	onoxide)	-	•	-	gr/bl	•		
CO (Carbon M PM (Particulate	onoxide)	2.60	gr/bhp-hr	0.007	gr/bl gr/bl	hp-hr		
CO (Carbon M PM (Particulate	onoxide) e Matter)	2.60 0.014	gr/bhp-hr gr/bhp-hr	0.007 0.014	gr/bl gr/bl gr/bl	hp-hr hp-hr		
CO (Carbon M PM (Particulate NMHC (Non-Me	onoxide) e Matter) ethane Hydrocarbons)	2.60 0.014 0.141	gr/bhp-hr gr/bhp-hr gr/bhp-hr gr/bhp-hr	0.007 0.014 0.002	gr/bl gr/bl gr/bl	hp-hr hp-hr hp-hr		
CO (Carbon M PM (Particulate NMHC (Non-Me NMHC + NOx EPA Engine Fa	onoxide) e Matter) ethane Hydrocarbons) amily: PJI	2.60 0.014 0.141 N/A	gr/bhp-hr gr/bhp-hr gr/bhp-hr gr/bhp-hr	0.007 0.014 0.002	gr/bl gr/bl gr/bl	hp-hr hp-hr hp-hr		
CO (Carbon M PM (Particulate NMHC (Non-Me NMHC + NOx EPA Engine Fa	onoxide) e Matter) ethane Hydrocarbons) amily: PJI e of Conformance: PJI	2.60 0.014 0.141 N/A DXL09.031	gr/bhp-hr gr/bhp-hr gr/bhp-hr gr/bhp-hr 3 3-020	0.007 0.014 0.002	gr/bl gr/bl gr/bl	hp-hr hp-hr hp-hr		

Styles Protection	UNITED STATES ENVIRONM 2023 MO CERTIFICATE WITH THE C	DEL YEAR OF CONFOR	МІТҮ	AND AIR QU	OFFICE OF TRANSPORTATION AND AIR QUALITY ANN ARBOR, MICHIGAN 48105			
Certificate Issued To: Dee (U.S.) Certificate Number: PJDXI	Manufacturer or Importer)			r, Division Director nce Division	Issue Date: 09/29/2022 Revision Date: N/A			
Model Year: 2023 Manufacturer Type: Origina Engine Family: PJDXL09.03	-		Mobile/Stationary Indicator: Both Emissions Power Category: 130<=kW Fuel Type: Diesel After Treatment Devices: Diesel Oxid Reduction Non-after Treatment Devices: Electro	lation Catalyst, Ammonia Slip Catal				

Pursuant to Section 111 and Section 213 of the Clean Air Act (42 U.S.C. sections 7411 and 7547) and 40 CFR Parts 60 and 1039, and subject to the terms and conditions prescribed in those provisions, this certificate of conformity is hereby issued with respect to the test engines which have been found to conform to applicable requirements and which represent the following engines, by engine family, more fully described in the documentation required by 40 CFR Parts 60 and 1039 and produced in the stated model year.

Non-After Treatment Device Installed

This certificate of conformity covers only those new compression-ignition engines which conform in all material respects to the design specifications that applied to those engines described in the documentation required by 40 CFR Parts 60 and 1039 and which are produced during the model year stated on this certificate of the said manufacturer, as defined in 40 CFR Parts 60 and 1039.

AL PROT

It is a term of this certificate that the manufacturer shall consent to all inspections described in 40 CFR 1068 and authorized in a warrant or court order. Failure to comply with the requirements of such a warrant or court order may lead to revocation or suspension of this certificate for reasons specified in 40 CFR Parts 60 and 1039. It is also a term of this certificate that this certificate may be revoked or suspended or rendered void *ab initio* for other reasons specified in 40 CFR Parts 60 and 1039.

This certificate does not cover engines sold, offered for sale, or introduced, or delivered for introduction, into commerce in the U.S. prior to the effective date of the certificate.

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2023	PJDXL09.0313	9.0	Diesel 8000						
SPECIAL	FEATURES & EMISSION O	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
Direct Inje Gas Reci	Air Cooler, Oxidation C ection, Electronic Contr rculation, Turbocharger tion-Urea, Ammonia O	ol Module, Exhaust , Selective Catalyst	Pump, Compressor, Generator Set, O Industrial Equipment						

The engine models and codes are attached.

CALIFORNIA AIR RESOURCES BOARD

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION				EXHAUST (g/kw-l	nr)		OF	PACITY (%	b)
	STANDARD CATEGORY		NMHC	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		CERT	0.004	0.10		0.01	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed on this <u>18th</u> day of October 2022.

Jolin U. Lang

Robin U. Lang, Chief *U* Emissions Certification and Compliance Division

Attachment: Engine Models EO #: U-R-004-0647 Family: PJDXL09.0313 Attachment Last Revised: 10/5/2022

					Displacement -		Peak Power -	Peak Power -	Peak Power -	Peak Power - Fue	el	Peak Torque -	Peak Torque -		el				
Model	Code	Trim	Config	Displacement	Units	Peak Power	Units	Speed (rpm)	Fueling	Units Peak Torque		ue Units	Speed (rpm)	Peak Torque - Fuel Units		OBD	GHG	Special	Notes
6090	6090HFG06A		I-6	9	Liters	345	kilowatt	1800	263.2	mm3/stroke	1830	N-m	1800	263.2	mm3/stroke	N/A	N/A		
6090	6090HFG06B		1-6	9	Liters	300	kilowatt	1500	269.8	mm3/stroke	1910	N-m	1500	269.8	mm3/stroke	N/A	N/A		
6090	6090HFG06C		1-6	9	Liters	326	kilowatt	1800	247.5	mm3/stroke	1731	N-m	1800	247.5	mm3/stroke	N/A	N/A		
6090	6090HFG06D		I-6	9	Liters	300	kilowatt	1500	269.5	mm3/stroke	1910	N-m	1500	269.5	mm3/stroke	N/A	N/A		
6090	6090HFG06E		1-6	9	Liters	273	kilowatt	1800	201.3	mm3/stroke	1448	N-m	1800	201.3	mm3/stroke	N/A	N/A		
6090	6090HFG06F		I-6	9	Liters	273	kilowatt	1500	243	mm3/stroke	1737	N-m	1500	243	mm3/stroke	N/A	N/A		
6090	6090HPRNT7		1-6	9	Liters	364	kilowatt	1800	277.6	mm3/stroke	1934	N-m	1800	277.6	mm3/stroke	N/A	N/A		
																_	_		
													_						
		_														_	_		
																	_		
																	_		
																	_		
		_														_	_		