EXHAUST EMISSION DATA SHEET

MQ POWER INDUSTRIAL GENERATOR SET



Model: KD75V

The engine used in this generator set is certified to comply with United States EPA Tier 1 and CARB Mobile Off-Highway emission regulations when tested per ISO 8178 D2.

ENGINE DATA

Make/Model:DEUTZ ~ TD520GEBore:4.25 in.(108 mm)Type:4-Cycle, In-Line, 4-Cylinder, DieselStroke:5.12 in.(130 mm)Aspiration:TurbochargedDisplacement:290 cid(4.7 liters)

Compression Ratio: 17.5:1

PERFORMANCE DATA

SAE Gross HP @ 1800 RPM (60 Hz) 119
Rated Load Fuel Consumption (gal/Hr) 6.1
Rated Load Exhaust Gas Flow (cfm) 618
Rated Load Exhaust Gas Temperature (F) 986

United States EPA - Mobile Off-Highway Tier I Limits - ≥100 BHP - ≤173 BHP		
Criteria Pollutant	Emission Requirements	Certified Engine Emissions
NOx (Oxides of Nitrogen as NO2)	6.90 gr/bhp-hr	6.26 gr/bhp-hr
HC (Total Unburned Hydrocarbons)	gr/bhp-hr	0.30 gr/bhp-hr
CO (Carbon Monoxide)	gr/bhp-hr	0.82 gr/bhp-hr
PM (Particulate Matter)	gr/bhp-hr	0.09 gr/bhp-hr

EPA Engine Family: 2DZXL07.1005 Effective Date: Year 2002

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.