EXHAUST EMISSION DATA SHEET

MQ POWER INDUSTRIAL GENERATOR SET

Model: KD250V



The engine used in this generator set is certified to comply with United States EPA Tier 2 and CARB Mobile Off-Highway emission regulations.

ENGINE DATA Make/Model: VOLVO ~ TAD1031GE Bore: 4.75 in. (120 mm) Type: 4-Cycle, In-Line, 6-Cylinder, Diesel Stroke: 5.51 in. (140 mm) Turbocharged, Charge Air Cooler Aspiration: Displacement: 585.8 cid (9.6 liters) Compression Ratio: 17.0:1 **PERFORMANCE DATA** SAE Gross HP @ 1800 RPM (60 Hz) 394 Rated Load Fuel Consumption (gal/Hr) 20.5 Rated Load Exhaust Gas Flow (cfm) 2225 Rated Load Exhaust Gas Temperature (F) 1040 United States EPA - Mobile Off-Highway Tier 2 Limits - ≥302 BHP - ≤602 BHP **Criteria Pollutant Emission Requirements Certified Engine Emissions** NOx + NMHC (*Combined) (*4.77) gr/bhp-hr (*4.40) gr/bhp-hr CO (Carbon Monoxide) 2.61 gr/bhp-hr 1.34 gr/bhp-hr 0.09 PM (Particulate Matter) 0.15 gr/bhp-hr gr/bhp-hr 4VPXL09.6ACB EPA Engine Family: EPA Certificate of Conformance: VPX-NR7-04-05 Year 2004 Effective Date:

Note: Engine operation with excessive air intake or exhaust restriction beyond factory published maximum limits, or with improper service maintenance, may result in higher emission levels.

Data And Specifications Subject To Change Without Notice MQ POWER