## **EXHAUST EMISSION DATA SHEET**

**MQ POWER GENERATOR SET** 

## Model: MQP450VO



## The engine used in this generator set is certified to comply with United States EPA Tier 2 and CARB Mobile Off-Highway emission regulations.

ENGINE DATA					
Manufacturer:	VOLVO		Bore:	5.67 in	144 mm
Model:	TAD1641GE		Stroke:	6.50 in	165 mm
Туре:	4-Cycle Diesel, D	irect Injection, I-6	Displacement:	984 in <sup>3</sup>	16.12 liters
Aspiration:	Turbocharger, Ch	arge Air Cooled, ECM	Compression F	Ratio:	15:1
PERFORMANCE DAT	<u> </u>				
SAE Gross HP @ 1800 RPM	1 (60 Hz)	757			
Rated Load Fuel Consumption	on (gal/Hr)	36.8			
	w (cfm)	3899			
Rated Load Exhaust Gas Flo					
Rated Load Exhaust Gas Flo Rated Load Exhaust Gas Te	. ,	893			
Rated Load Exhaust Gas Te	mperature (F)	893 Mobile Off-Highwa	y Tier 2 Limits	6 - ≥751	ВНР
Rated Load Exhaust Gas Te	mperature (F) States EPA -		-	s - ≥751 Engine E	
Rated Load Exhaust Gas Te	mperature (F) States EPA - EI	Mobile Off-Highwa	-		missions
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as HC (Total Unburned Hydroca	States EPA -         Etail         NO2)	Mobile Off-Highwa	Certified 4.03	Engine E	missions
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as	States EPA -         Etail         NO2)	Mobile Off-Highwa mission Requirements 7 gr/bhp-hr NOx + HC)* Combined	Certified 4.03	Engine E gr/bhp-hr	missions mbined
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as HC (Total Unburned Hydroca	mperature (F)         States EPA -         En         NO2)       4.7         arbons)       (1)	Mobile Off-Highwa mission Requirements 7 gr/bhp-hr NOx + HC)* Combined 61 gr/bhp-hr	Certified 4.03 (NOx -	Engine E gr/bhp-hr + HC)* Cor	missions mbined
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as HC (Total Unburned Hydroca CO (Carbon Monoxide)	States EPAEnNO2)4.7arbons)(10.1	Mobile Off-Highwa mission Requirements 77 gr/bhp-hr NOx + HC)* Combined 61 gr/bhp-hr	Certified 4.03 (NOx - 0.52	Engine E gr/bhp-hr + HC)* Cor gr/bhp-hr	missions mbined
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as HC (Total Unburned Hydroca CO (Carbon Monoxide) PM (Particulate Matter)	Marbons) (I States EPA - Interpretation (I States EPA - Interpretation (I States Interpretation (I States Interpretatio	Mobile Off-Highwa mission Requirements 7 gr/bhp-hr NOx + HC)* Combined 61 gr/bhp-hr 5 gr/bhp-hr	Certified 4.03 (NOx - 0.52	Engine E gr/bhp-hr + HC)* Cor gr/bhp-hr	missions mbined
Rated Load Exhaust Gas Te United Criteria Pollutant NOx (Oxides of Nitrogen as HC (Total Unburned Hydroca CO (Carbon Monoxide) PM (Particulate Matter) EPA Engine Family:	mperature (F) States EPA - NO2) Arbons) (( 2.6 0.1 8VPX nce: VPX-n	Mobile Off-Highwa mission Requirements 7 gr/bhp-hr NOx + HC)* Combined 61 gr/bhp-hr 5 gr/bhp-hr L16.1ACB	Certified 4.03 (NOx - 0.52	Engine E gr/bhp-hr + HC)* Cor gr/bhp-hr	missions mbined

or with improper service maintenance, may result in higher emission levels.

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours) 8000			
2008	8VPXL16.1ACB	16.12	Diesel				
	FEATURES & EMISSION			TYPICAL EQUIPMENT APPLICATION			
Direct Dies	el Injection, Turbocharg Engine Control Mo	er, Charge Air Cooler, odule	Generator				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION		EXHAUST (g/kW-hr)					OPACITY (%)		
CLASS	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
kW > 560	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	N/A	N/A	N/A
	1	FEL	-	-	6.0	-	0.17	-	-	-
		CERT	-	-	5.4	0.7	0.10	-	-	-

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2007.

Æ

Annette Hebert, Chief Mobile Source Operations Division

## Engine Model Summary Form

AB Volvo Penta							
Nonroad Cl					1 0 5 1		
8VPXL16.1ACB			Atte	Attachment		$ \mathbf{N} - \mathbf{R} - \mathbf{P} \mathbf{K} - \mathbf{P} \mathbf{O}$	
TAD 164XGE						u k	
New Submission							
2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
TAD1642GE	809@1800	404		231818	NA	- NA	ECM, CAC, TC, DPJ
TAD1641GE	757@1800	374		2230	NA	NA	
	Nonroad Cl 8VPXL16.1ACB TAD 164XGE New Submission 2.Engine Model TAD1642GE	Nonroad Cl 8VPXL16.1ACB TAD 164XGE New Submission 2.Engine Model 3.BHP@RPM (SAE Gross) TAD1642GE 809@1800	Nonroad CI         & 8VPXL16.1ACB         TAD 164XGE         New Submission         2.Engine Model         3.BHP@RPM (SAE Gross)         4.Fuel Rate: mm/stroke @ peak HP (for diesel only)         TAD1642GE         809@1800	Nonroad CI 2. 8VPXL16.1ACB TAD 164XGE New Submission 2.Engine Model 3.BHP@RPM (SAE Gross) 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) TAD1642GE 809@1800 404	Nonroad Cl       AHachment         & 8VPXL16.1ACB       AHachment         TAD 164XGE       AHachment         New Submission       4.Fuel Rate:       5.Fuel Rate:         2.Engine Model       3.BHP@RPM (SAE Gross)       4.Fuel Rate:       5.Fuel Rate:         TAD1642GE       809@1800       404       2388	Nonroad Cl       Attachment 1 of 1         & 8VPXL16.1ACB       Attachment 1 of 1         TAD 164XGE       New Submission         2.Engine Model       3.BHP@RPM (SAE Gross)       4.Fuel Rate: mm/stroke@peak HP (for diesel only)       5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)       7.Fuel Rate: mm/stroke@peak torque         TAD 1642GE       809@1800       404       2388       NA	Nonroad Cl         & 8VPXL16.1ACB         TAD 164XGE         New Submission         2.Engine Model       3.BHP@RPM (SAE Gross)         4.Fuel Rate: mm/stroke@peak HP (for diesels only)       5.Fuel Rate: (bs/hr)@peak HP (for diesels only)       7.Fuel Rate: mm/stroke@peak (SEA Gross)         TAD1642GE       809@1800       404       2388       NA