



MECHANICAL RIDE-ON TROWELS DRIVE SHAFT GUIDE

Model #	Clutch Type	Left Axle	Length	Right Axle	Length	Center Cross Shaft	* Full Assy.
HHNG-4, 5	Hilliard	23477	7.44"	23922	10"	30108	23921-SK
EHHNK5							
HHN31	Comet	23450	7.81"	23451	9.63"	32581-SK	20062
	Hilliard	23450	7.81"	23451	9.63"	30108	30089
HHN34	Comet	23450	7.81"	23451	9.63"	32581-SK	21493
	Hilliard	23450	7.81"	23451	9.63"	30108	30089
HHXD5	Comet	23140	7.70"	23140	7.70"	N/A	N/A
	Hilliard	23140	7.70"	23140	7.70"	30106	30090
HHXDF-4, 5	Hilliard	23477	7.44"	23779	7.45"	30357-SK	N/A
HHXG5	Comet	23140	7.70"	23140	7.70"	N/A	N/A
	Hilliard	23140	7.70"	23140	7.70"	30106	30090
HTN-27, 28	CVTECH	23636	8.50"	23630	10.75"	23632	* 23631
HTN-27, 28	Comet	23636	8.50"	23630	10.75"	32581-SK	21494
JWN	CVTECH	23477	7.44"	23477	7.44"	* 23485-SK	N/A

*** See Notes**

Notes:

* Full Assy... L/R Axles – Cross Shaft – Lower Pulley

* 23631 Without Axles

* 23485-SK Center cross shaft only – with CV TECH Clutch installed, use 23478