MANDATORY UPDATE INFORMATION

Date: 03/23/18

To: TRLR45/TRLR70US Trailer Owners

From: Multiquip Product Department

Subject: Trailer Frame Reinforcement — Mandatory Update

Dear Multiquip Customer,

Our records indicate that your company purchased one or more TRLR45 or TRLR70US Trailers.

Multiquip deems the design of these trailers to be adequate in their current state to handle the specified GVWR. However, in the interest of public safety, due to unintentional overload as a foreseeable misuse, we are enhancing the safety factor of the trailer design by mandating the installation of this update.

The accompanying bulletin lists the problems and explains the actions required to correct these problems.

Failure to repair may compromise structural integrity of the trailer frame when unintentionally overloaded.

If this trailer has been resold, please forward this bulletin to the new owner.

Your prompt attention to this matter is appreciated. If you have questions, please contact the Multiquip Technical Support Department at 800-478-1244 or techsupport@multiquip.com.

PARTS ORDERING INFORMATION

YOU MUST PLACE A PARTS ORDER WITHTHE MULTIQUIP PARTS DEPARTMENT TO ENSURE PROPER SHIPMENT. Upon placing the order, the parts needed will be shipped to you.

- Parts order form has been enclosed for your convenience.
- Use Multiquip's SmartEquip[™] Online Parts Order System for faster service.

WARRANTY INFORMATION

Campaign: Reference No. TL20180306

Option 1: To expedite warranty reimbursement, submit warranty claim online with Multiquip's E-Warranty application. Contact the Multiquip Warranty Department for username and password.

Option 2: Fill out the enclosed Application for Warranty Consideration form and fax to the MQ Warranty Department.

Labor Allowance: 2.0 hour total flat rate for trailer jack crossmember gusset installation.





Parts Order Form – TRLR45/TRLR70US Trailer Update

Warranty Campaign TL20180306 Parts Order Form

Please Print Clearly and Provide Requested Information as Accurately as Possible.

Y. PART NUMBER	DESCRIPTION
49941-02	Gusset, Jack Crossmember, TRLR45
del No. TRLR45	Serial No.
4 NT	Acct. No
nact ivallic.	
y:	Zip Code

Return Today By Fax

Toll Free Fax: 800/672-7877 • Direct Fax: 310/637-3284
Toll Free Phone: 800/427-1244 • Direct Phone: 310/537-3700
Export Parts Orders Fax: 310/537-3371



Parts Order Form – TRLR45/TRLR70US Trailer Update

Warranty Campaign TL20180306 Parts Order Form

Please Print Clearly and Provide Requested Information as Accurately as Possible.

TY. PART NUMBER	DESCRIPTION		
2 49927-02	Gusset, Jack Crossmember, TRLR70US		
Model No. TRLR70US	Serial No.		
Sold to Company:			
~ · · · · · · · · · · · · · · · · · · ·			
Ship to Company:			
Contract No.			
Ctuant Addungs.			
~			
State/Province:	Zip Code		

Return Today By Fax

Toll Free Fax: 800/672-7877 • Direct Fax: 310/637-3284
Toll Free Phone: 800/427-1244 • Direct Phone: 310/537-3700
Export Parts Orders Fax: 310/537-3371

Application for Warranty Consideration

NOTE: THIS IS NOT A WARRANTY APPROVAL until

Your WO Ref #



MULTIQUIP INC. 18910 WILMINGTON AVENUE • CARSON CA 90746 POST OFFICE BOX 6254 • CARSON, CA 90749 Phone: 800-421-1244 • FAX: 310-943-2249

E-mail: MQWarranty@Multiquip.com

omerwise	specified.							
Account No	D.		Unit Model	#		Purchase	e Date:	
Dealer Name:			Serial #		Resale Date/in Service Date:			
Address:			Hours Mete	Hours Meter Reading:		Date of Failure:		
City/State/Zip:			Engine Model #			Date of Repair:		
Contact:			Engine Ser	al#		Date of C	Claim:	
Phone #		Fax #		Email:				
			S REPLAC					
Qty / Hrs			Invoice or Packing L Replacement				Extended Amount	
PRIMARY	FAILED PAR	T — List the defective part repl	laced (the	part that car	used the	warranta	able failure)	
		ALL OTHER PARTS— List all o	ther parts	used to cor	nplete th	e repair		
			•		•	•		
	le (allowed on lipment only):	Jobsite Address:		I				
	Millage:							
	Freight:							
							Total \$	
				NOTE: Lab subject for considerat MQ approv	ion by	LABOR HOURS	LABOR RATE	AMOUNT
FSM Approval Ref # (If assigned by Field Service Mgr.)				Lal		2.0		
	•			Pa	rts			
				Mis	sc.			
) Reason for Warranty Claim				TOTA	AL CLAIM \$	
Problem/	Cause:							
Domodu /	Notos							
Remedy/	Notes:							
PHOTOS N	MAY BE REQUE	CTIVE PARTS "MUST" BE KEPT FO STED OR DEFECTIVE ITEM(S) FOR efective item(s) to Multiquip "only"	R MULTIQUI	P REVIEW AN				

^{***}On-line Warranty Application is also available; please contact MQ Warranty Department to obtain access***

Product Group: Date Issued:		Expiration Date:	Service Bulletin No.		
Trailers	03/23/18	03/23/19	TL20180306		
Bulletin Type		Models/Series Affected:			
X Mandatory		TRLR45			
Wandatory		VIN L021853, L021854, L021855, L021856, L021857, L021858, and L021873			
Information Only		TRLR70US			
D		VIN L021931, L021932, L021933, L021934, L021936,			
Recommended Ch	ange	and L021937			

Details
Problem:
Improve existing trailer design.
Solution:
Install trailer reinforcement gussets.

Parts Information

Table 1. Gusset Installation Kit						
Item No. Part No. Description		Qty.	Remarks			
1	49941-02	Gusset, Jack Crossmember, TRLR45	2	TRLR45 only		
1	49927-02	Gusset, Jack Crossmember, TRLR70	2	TRLR70 only		




Figure 1. Gussets

WORK SAFELY!

Only a *certified welder* with proper training should perform this installation. Follow all shop safety rules while performing this installation.

NOTICE

If gussets are already installed on the jack crossmember of your trailer frame, please disregard this bulletin.

NOTICE

Failure to repair may compromise structural integrity of the trailer frame when unintentionally overloaded.

SAFETY

- Perform all work in a well-ventilated area to prevent inhalation of dust and toxic fumes.
- **DO NOT** use chlorinated solvents in areas where welding will take place.
- ALWAYS properly dispose of paint and solvents.

REQUIRED TOOLS

- Welder
- Locking C-clamp
- Approved respirator
- Welding face shield
- Safety glasses
- Gloves
- Hard hat
- Grinder
- Flat black spray paint

PREPARATION

- Make sure the gussets are accounted for before beginning this installation procedure. Refer to Table 1 and Figure 1.
- Place the trailer in an area free of dirt and debris. Make sure it is on secure, level ground with chock blocks underneath each wheel to prevent the trailer from rolling.

DECAL REMOVAL

NOTICE

Due to **excessive heat** during the welding process, the possibility exists that the **Vehicle Identification Number (VIN)** and **tire pressure** decals may become damaged.

NOTICE

Record the **entire** Vehicle Identification Number (VIN) displayed on the decal before removing the decal.

Replacement VIN and tire pressure decals will be provided only after a claim has been filed with the MQ Warranty Department.

 Record the entire Vehicle Identification Number displayed on the VIN decal. Also record the last five digits of the VIN number which are stamped into the trailer frame (Figure 2).




Figure 2. VIN/Tire Pressure Decal Removal

2. Remove the VIN and tire pressure decals (Figure 2).

PAINT REMOVAL

1. Using a grinder, remove the paint from the areas to be heated during welding (Figure 3).

NOTICE

Failure to properly remove the powder coat prior to welding may cause excessive porosity in the welds.




Figure 3. Paint Removal

CAUTION

If the paint cannot be removed, wear an approved respirator before heating or welding to prevent inhalation of hazardous material.

WELDING

1. Place the gusset (P/N 49941-02, P/N 49927-02, or P/N 49867-02) between the jack crossmember and drawbar rail as shown in Figure 4.




Figure 4. Gusset Placement

2. Once the gusset is correctly positioned, secure it in place with a locking C-clamp as shown in Figure 5.




Figure 5. Secure Gusset with Clamp

3. Weld the gusset to the trailer frame (Figure 6).




Figure 6. Gusset Welding

- 4. Repeat steps 1–3 with the second gusset on the opposite side of the trailer frame.
- 5. At the completion of the welding process, remove any flux, burrs, or rough edges from the welding area.

PAINTING

NOTICE

Allow the welded area to cool before painting.

1. Clean all welded areas on the trailer frame with a wire brush, then paint the welding areas with **flat black spray paint** (Figure 7).




Figure 7. Paint Welding Areas

VIN AND TIRE PRESSURE DECAL REPLACEMENT

NOTICE

The steps below cannot be completed until your warranty claim has been processed. Once your claim has been processed and your VIN number has been verified, replacement VIN and tire pressure decals will be sent to you.

- Compare your new replacement VIN decal identification number with the number that was recorded earlier. If the numbers match, proceed to step 2. If the numbers DO NOT match, contact the MQ Warranty Department.
- 2. Clean the decal location on the trailer surface with isopropyl alcohol.
- 3. Place the replacement VIN and tire pressure decals onto the trailer as shown in Figure 8.




Figure 8. Decal Replacement

HERE'S HOW TO GET HELP

PLEASE HAVE THE MODEL AND SERIAL NUMBER ON-HAND WHEN CALLING

UNITED STATES

Multiquip Corporate Office

18910 Wilmington Ave. Carson, CA 90746

Contact: mg@multiquip.com

Service Department

800-421-1244 310-537-3700

Technical Assistance

800-478-1244

CANADA

Multiquip

4110 Industriel Boul. Laval, Quebec, Canada H7L 6V3 Contact: infocanada@multiquip.com

Tel. (800) 421-1244

Fax (310) 537-3927

Fax: 310-943-2238

Tel: (450) 625-2244

Tel: (877) 963-4411

Fax: (450) 625-8664

MQ Parts Department

800-427-1244 310-537-3700

Warranty Department

800-421-1244 310-537-3700

Fax: 310-943-2249

Fax: 800-672-7877

UNITED KINGDOM

Multiquip (UK) Limited Head Office

Unit 2, Northpoint Industrial Estate, Globe Lane.

Dukinfield, Cheshire SK16 4UJ Contact: sales@multiquip.co.uk

Tel: 0161 339 2223

Fax: 0161 339 3226

© COPYRIGHT 2017. MULTIQUIP INC.

Multiquip Inc and the MQ logo are registered trademarks of Multiquip Inc. and may not be used, reproduced, or altered without written permission. All other trademarks are the property of their respective owners and used with permission.

The information and specifications included in this publication were in effect at the time of approval for printing. Illustrations, descriptions, references and technical data contained in this document are for guidance only and may not be considered as binding. Multiquip Inc. reserves the right to discontinue or change specifications, design or the information published in this publication at any time without notice and without incurring any obligations.

Your Local Dealer is:

