



The information and specifications included in this publication were in effect at the time of approval for printing. Illustrations, descriptions, references and technical data contained in this document are for guidance only and may not be considered as binding. Multiquip Inc. reserves the right to discontinue or change specifications, design or the information published in this publication at any time without notice and without incurring any obligations.

TROWEL WEIGHTS AND PRESSURES

The below reference table provides the following information

- ✓ Trowel weight with handle
- ✓ Blade pressure in pounds per square foot (psf)
- ✓ Panning pressure in pounds per square foot (psf)
- ✓ Blade Pressure in pounds per square inch (psi)
- ✓ Panning Pressure in pounds per square inch (psi)

Note: Pan Weight Specifications

24" (10 lbs.) | 36" (40 lbs.) | 46" (65 lbs.) | 60" (108 lbs.)

WALK-BEHIND TROWELS

@ flat (zero pitch)

Model	Dry Weight with Handle	Handle Options	Weight with Pan (lbs.)	Blade Pressure (psi)	Blade (psf)	Panning Pressure (psi)	Pan (psf)
CA4HM / CA5BM	145	QPHAFC	155	0.980	141.08	0.343	49.34
CA4HC / CA4BC	145	QPHAFC / STHAC	155	0.980	141.08	0.343	49.34
CA5BC	145	QPHAFC	155	0.980	141.08	0.343	49.34
J3036H55	168	SXH	208	0.435	62.69	0.204	29.43
J3036H55	180	QXH	220	0.466	67.16	0.216	31.12
J36E2	166	W/H	N/A	0.430	61.94	N/A	N/A
J36H55 / J36B65	183	SXH	223	0.474	68.28	0.219	31.55
J36H55 / J36B65	195	QXH	235	0.505	72.76	0.231	33.25
J36H55 / J36B65	183	SXHP	223	0.474	68.28	0.219	31.55
J36H55 / J36B65	195	QXHP	235	0.505	72.76	0.231	33.25
J36H90H	212	SXH	252	0.549	79.10	0.248	35.65
J36H90H	224	QXH/QXHP	264	0.580	83.58	0.259	37.35
J36H90H	212	SXHP	252	0.549	79.10	0.248	35.65
J36KDF	259	SXH	299	0.671	96.64	0.294	42.30
J36KDF	270	QXH	310	0.700	100.75	0.305	43.86
J36S60	190	SXH	230	0.492	70.90	0.226	32.54
J36S60	202	QXH	242	0.523	75.37	0.238	34.24
J36S60	190	SXHP	230	0.492	70.90	0.226	32.54
J36S60	202	QXHP	242	0.523	75.37	0.238	34.24
B46H90 / B46B90	265	SXH	330	0.541	77.94	0.199	34.24
B46H90 / B46B90	272	QXH	337	0.556	80.00	0.203	29.20
B46H90 / B46B90	265	SXHP	330	0.541	77.94	0.199	28.59
B46H90 / B46B90	272	QXHP	337	0.556	80.00	0.203	29.20
B46H11H	265	SXH/SXHP	330	0.541	77.94	0.199	28.59
B46H11H	275	QXH/QXHP	340	0.556	80.00	0.205	29.46
B46KDF	287	SXH	352	0.586	84.41	0.212	30.50
B46KDF	309	QXH	374	0.631	90.88	0.225	32.41
HDA48413H	340	SXHD	405	0.694	100.00	0.224	32.23
HDA48413H	352	QXHD	417	0.719	103.53	0.230	33.18

© COPYRIGHT 2020, MULTIQUIP INC, Rev. 3 (04132022)



The information and specifications included in this publication were in effect at the time of approval for printing. Illustrations, descriptions, references and technical data contained in this document are for guidance only and may not be considered as binding. Multiquip Inc. reserves the right to discontinue or change specifications, design or the information published in this publication at any time without notice and without incurring any obligations.

TROWEL WEIGHTS AND PRESSURES

The below reference table provides the following information

- ✓ Trowel weight with handle
- ✓ Blade pressure in pounds per square foot (psf)
- ✓ Panning pressure in pounds per square foot (psf)
- ✓ Blade Pressure in pounds per square inch (psi)
- ✓ Panning Pressure in pounds per square inch (psi)

Note: Pan Weight Specifications

24" (10 lbs.) | 36" (40 lbs.) | 46" (65 lbs.) | 60" (108 lbs.) | 70" (172 lbs.)

Note: Dry-Weight of Ride-On Trowel includes 200 lb Operator & Duel Fuel models includes empty LPG tank

RIDE-ON TROWELS

Model	Dry Weight	Weight with Pans (lbs.)	@ flat (zero pitch)		Panning Pressure (psi)	Pan (psf)
			Blade Pressure (psi)	Blade (psf)		
PRX	3822	4166	N/A	N/A	0.55	79.2
STXDF	2825	3041	1.493	214.982	0.538	77.438
STXD6i	2363	2579	1.249	179.824	0.456	65.674
STX55Y	2349	2565	1.241	178.759	0.454	65.317
STX6H	2706	2922	1.430	205.926	0.517	74.408
HTXG6DF	2335	2465	1.496	215.406	0.681	98.079
HTXD6i	2275	2405	1.457	209.871	0.665	95.692
HTX6H	2447	2607	1.568	225.738	0.720	103.729
HTX-EHTX	1920	2050	1.312	188.93	0.617	88.81
HHXD5	1673	1803	1.143	164.62	0.542	78.11
HHXDF5	1825	1955	1.247	179.58	0.588	84.70
HHXG5	1599	1729	1.093	157.34	0.520	74.91
LD6	1056	1136	1.725	248.74	0.558	80.36
EHHNK5	1888	2018	1.290	185.78	0.607	87.43
HHNG5	1282	1412	0.876	126.15	0.425	61.17
HHN 34	1292	1422	0.883	127.13	0.428	61.61
HHN 31	1242	1372	0.849	122.21	0.379	54.59
HTO 31	1242	N/A	1.061	152.77	N/A	N/A
HTN 27	1060	1190	0.905	130.38	0.358	51.56
HTN 28	1060	1190	0.905	130.38	0.358	51.56
HTN 31	1200	1330	1.025	147.60	0.400	57.62
JTO	640	N/A	1.046	150.59	N/A	N/A
JWN 24	985	1065	1.609	231.76	0.523	75.33
JTN 20	768	848	1.255	180.71	0.417	59.98

© COPYRIGHT 2020, MULTIQUIP INC., Rev. 3 (04132022)